

BATTERIES

5-200 Ah



HIGH EFFICIENCY



CLEAN ENERGY



ECO-FRIENDLY TECHNOLOGY



IP23



NECRON provides produced types of VRLA, OPzS, Gel, Ni-Cd, Li-ion according to the international standards. High quality NECRON's batteries approved by CE, UL, TSE, EUROBAT certifications save running critical loads at industrial environment.

NECRON always supplies the best products and cooperates with the world's largest factories for battery groups

TSE: Turkish Standards Institute
UL: Underwriters Laboratories
CE: Conformity of European
EUROBAT: European Battery

*There is no mandatory keeping each certification together for same battery.

Uluslararası standartlara uygun olarak üretilmiş Bakımsız Kuru Tip, OPzS, Jel, Ni-Cd, Li-Ion tipi aküler sunar. CE, UL, TSE, EUROBAT sertifikalarının tasdiklediği yüksek kaliteli besleme gücü, işiniz için kritik yüklerin çalışmasını korur.

NECRON her zaman en iyi ürünü sunar ve akü grupları için dünyanın en büyük fabrikaları ile işbirliği yapar.

TSE: Türk Standartları Enstitüsü
UL: Underwriters Laboratories
CE: Avrupa Onayı
EUROBAT: Avrupa Akü Sertifikasyonu

*Aynı akü için her sertifikanın bir arada bulunma zorunluluğu yoktur.

Capacity (Ah)	Nominal Voltage	Internal Res. (mΩ)	Length (mm)	Width (mm)	Height (mm)	Total Height	Terminal		Weight (kg)
							Type	Position	
5.0	12	33	90	70	101	107	T1	C	1.67
6.0	12	32	90	70	101	107	T1	C	1.82
5.0	12	34	140	48	102	103	+T2 / -T1	C	1.67
6.0	12	32	140	48	102	103	+T2 / -T1	C	1.82
6.5	12	24	151	52	94	99	T2/T1	F	1.92
6.5	12	24	151	51	95	100	+T2 / -T1	F	1.92
6.0	12	28	151	65	94	100	T1/T2	F	2.10
7.0	12	25	151	65	94	100	T1/T2	F	2.0
7.2	12	25	151	65	94	100	T1/T2	F	2.25
7.5	12	24	151	65	94	100	T1/T2	F	2.32
8	12	20	151	65	94	100	T1/T2	F	2.40
9.0	12	19	151	65	94	100	T1/T2	F	2.50
10.0	12	22	151	65	111	117	T2/T1	F	2.85
10.0	12	22	151	98	95	101	T2	F	3.50
12.0	12	19	151	98	95	101	T2	F	3.60
15.0	12	19	160	76	159	162	T3	C	4.5
15.0	12	18	181	77	167	167/167	T3/T8	D	5
17.0	12	17	181	77	167	167/167	T3/T8	D	5.2
18.0	12	17	181	77	175	175/175	T3/T8	D	5.4
20.0	12	15	181	77	167	167/167	T3/T8	D	5.8
22.0	12	14	181	77	166	166	T8	D	6.3
24.0	12	12	166	175	125	125/125	T3/T8	D	8.0
24.0	12	12	165	125	175	182/175	T6/T8	D	8.1
26.0	12	12	176	165	127	127	T3	D	8.1
28.0	12	10	166	175	125	125/125	T3/T8	D	8.8
33	12	10	195	130	155	180/166	T7/T9	C	10.2
35	12	9.7	195	130	155	180/166	T7/T9	C	10.7
34	12	10	310	77	166	172/180	T2/T3	D	9.5
38	12	9.7	197	165	170	170/170	T4/T9	D	12.5
40	12	9.5	197	165	170	170/170	T4/T9	D	13.3
60	12	5.7	260	168	211	233/214	T5/T9	C	19.5
70	12	5.5	260	168	211	233/214	T5/T9	C	22.2
75	12	5.5	260	168	211	233/214	T5/T9	C	23.0
80	12	5.4	260	168	211	233/214	T5/T9	C	24.0
85	12	5.3	260	168	211	233/214	T5/T9	C	25.0
65	12	6	350	167	179	186	T5/T9	C	21.2
70	12	5.8	350	167	179	186	T5/T9	C	21.5
75	12	5.6	350	167	179	186	T5/T9	C	22.5
78	12	5.5	350	167	179	186	T5/T9	C	23.5
80	12	5.4	350	169	179	186	T5/T9	C	24.0
65	12	6	350	166	179	174	T17/T9	D	20.4
65	12	6	350	173	179	170	T9	D	21.2
90	12	5	330	171	214	224/220	T5/T9	C	27.0
100	12	4.5	330	173	233	224/220	T5/T9	C	30.5
150	12	3.5	487	175	280	285	T11	C	46.0
200	12	3	494	206	209	235	T20/T11	E	57

Voltage: 12V Capacity: 28Ah - 200Ah
Life Span: 20°C - 25°C for 10 years

Voltage: 12V Capacity: 5Ah - 26Ah
Life Span: 20°C - 25°C for 5 years